

Canister Extractors

EX-CAN-15LP / EX-CAN-15HPH



Portable low and adjustable pressure canister carpet extractors make quick work in tight areas.

Control your clean

Pick the model that meets your cleaning needs. Prevent over-wetting with an adjustable water pressure unit with built-in heater to increase cleaning power or choose the standard 100 psi model.

Simple maintenance, easy mobility

Get quick, easy access to working parts with the convenient clamshell design. The extractor's large rear wheels increase mobility and allow for easier transportation on stairs.

Low cost life-cycle

Strong and robust construction means years of dependable use. The unique bladder design maximizes solution/recovery while minimizing the unit's footprint.



Key Benefits

- Straightforward, simple design makes this unit easy to use and maneuver
- Patented bladder design keeps machine compact
- Choose from a low pressure (100 psi) unit or adjustable pressure (0-250 psi) with heat extractor



Canister Extractors

EX-CAN-15LP / EX-CAN-15HPH



Features	Specifications*	
Product Name	EX-CAN-15 LP (low pressure)	EX-CAN-15 HPH (high pressure w/ heat)
Solution System Solution pump pressure Solution pump voltage Solution pump amps Solution pump open flow rate	100 psi / 6.9 bar 120 V 1 A 1.8 gpm / 6.81 L/min	0-250 psi / 0-17.22 bar (variable) 120 V 5 A 2.4 gpm / 9 L/min
Heat Exchanger Description	—	Cast aluminum, hairpin element cast into aluminum, surface mount thermostat; preset to 170°F (76.6°C) for safety
Vacuum System Airflow at 2 in / 50 mm orifice Water lift at sealed orifice Vacuum motor type Vacuum motor power Vacuum motor stages Vacuum motor voltage Vacuum motor amps	101 ft ³ / 2.8 m ³ /h 137 in / 3480 mm (LP) / 134 in / 3403 mm (HPH) Single speed, tangential discharge, 5.7 in / 145 mm diameter, dual ball bearings, epoxy painted fan case; recognized by UL 1.66 hp / 1.23 kW (LP) / 2.5 hp / 1.87 kW (HPH) 3 stage 120 V AC 13 A (LP) / 10 A (HPH)	
Tank Capacity Solution tank capacity Recovery tank capacity	15 gal / 56.7 L 19 gal / 71.9 L	
Chassis/Body Construction Construction type Caster diameter (locking) Wheel diameter	Rotationally-molded polyethylene 4 in / 100 mm 12 in / 305 mm	
Power Cord Power cord length Power cord type	25 ft / 7.6 m, 1 cord / 2 cord (EX-CAN-15 HPH) 14 gauge 3 wire SJTO, recognized by UL and CSA, safety yellow, detachable	
Standard Tools/Accessories Tool/accessory description	Low pressure (EX-CAN-15 LP) / High pressure (EX-CAN-15 HPH) 13 in / 330 mm floor tool with three spray jets, stainless steel wand/shoe, 15 ft x 1.5 in / 4.5 m x 380 mm vacuum hose, 15 ft x 3/8 in 4.5 m x 90 mm solution hose. Contact your sales representative or authorized distributor for information on additional accessories.	
Dimensions/Weight/Sound Level Length/Width/Height/Weight/Sound	L: 38 in / 965 mm, W: 19 in / 482 mm, H: 38 in / 965 mm, Wt: 110 lb / 49.8 kg (LP) 145 lb / 65.7 kg (HPH), 82 dBA	
Approvals	CSA	
Warranty	See your sales representative or authorized distributor for complete warranty details.	

*Specifications subject to change without notice