

Click the model number below...

1510 (battery)

1530 (cord-electric)



Model 1510 Specifications

AUTOMATIC CARPET EXTRACTOR

Feature		English / Metric
Brush System		
Brush length		19-inch/ 482 mm
Brush type		Nylon
Brush RPM		2800
Motor power		(2) 0.2 hp/ 0.15 kW
Motor RPM		1800
Drive System		
Top interim cleaning speed		100 fpm/ 30 mpm
Top deep cleaning speed		50 fpm/ 15 mpm
Max. ramp while cleaning		5 degree
Productivity		
Theoretical max. per hour: interim cleaning		11,000 ft ² / 1,022 m ²
Deep cleaning		5,500 ft ² / 511 m ²
Machine Dimensions		
Length		50-inch / 1270 mm
Machine Width		22-inch / 558 mm
Height		42-inch / 1066 mm
Weight (batteries installed)		656 lb / 298 kg
Solution & Recovery System		
Solution tank capacity		21 gallon/ 72 liter
Recovery tank capacity		21 gallon/ 72 liter
Airflow		Dual 69 cfm/ 1.96 m ³ vac motors
Waterlift		(2) 68-inch/ 1727 mm vac motors
Vacuum motor power		(2) 0.89 hp/ 0.66 kW vac motors
Vacuum motor stages		(2) 3 stage vac motors
Power Consumption		
Total power consumption		55 amps
Battery run time		3 hours
Battery configuration		4-6 volt 235 AH batteries
Sound Level		
Operator's ear		72 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	



Model 1530 Specifications

AUTOMATIC CARPET EXTRACTOR

Feature		English / Metric
Brush System		
Brush length		19-inch/ 482 mm
Brush type		Nylon
Brush RPM		2800
Motor power		0.25 hp/ 0.19 kW
Motor RPM		1800
Drive System		
Top interim cleaning speed		100 fpm/ 30 mpm
Top deep cleaning speed		50 fpm/ 15 mpm
Max. ramp while cleaning		5°
Productivity		
Theoretical max. per hour: interim cleaning		11,000 ft ² / 1,022 m ²
Deep cleaning		5,500 ft ² / 511 m ²
Machine Dimensions		
Length		50-inch / 1270 mm
Machine Width		22-inch / 558 mm
Height		42-inch / 1066 mm
Weight		395 lb / 180 kg
Solution & Recovery System		
Solution tank capacity		30 gallon/ 113.6 liter
Recovery tank capacity		21 gallon/ 72 liter
Airflow		99 cfm/ 2.80 m ³ per min
Waterlift		117-inch/ 2971 mm
Vacuum motor power		1.63 hp/ 1.22 kW
Vacuum motor stages		Single 3 stage
Power Consumption		
Total power consumption		14 amps
Sound Level		
Operator's ear		72 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	