

**Click the model number below...**

1510 (battery)

1530 (cord-electric)



# Model 1510 Specifications

## AUTOMATIC CARPET EXTRACTOR

Feature		English / Metric
<b>Brush System</b>		
Brush length		19-inch/ 482 mm
Brush type		Nylon
Brush RPM		2800
Motor power		(2) 0.2 hp/ 0.15 kW
Motor RPM		1800
<b>Drive System</b>		
Top interim cleaning speed		100 fpm/ 30 mpm
Top deep cleaning speed		50 fpm/ 15 mpm
Max. ramp while cleaning		5 degree
<b>Productivity</b>		
Theoretical max. per hour: interim cleaning		11,000 ft <sup>2</sup> / 1,022 m <sup>2</sup>
Deep cleaning		5,500 ft <sup>2</sup> / 511 m <sup>2</sup>
<b>Machine Dimensions</b>		
Length		50-inch / 1270 mm
Machine Width		22-inch / 558 mm
Height		42-inch / 1066 mm
Weight (batteries installed)		656 lb / 298 kg
<b>Solution &amp; Recovery System</b>		
Solution tank capacity		21 gallon/ 72 liter
Recovery tank capacity		21 gallon/ 72 liter
Airflow		Dual 69 cfm/ 1.96 m <sup>3</sup> vac motors
Waterlift		(2) 68-inch/ 1727 mm vac motors
Vacuum motor power		(2) 0.89 hp/ 0.66 kW vac motors
Vacuum motor stages		(2) 3 stage vac motors
<b>Power Consumption</b>		
Total power consumption		55 amps
Battery run time		3 hours
Battery configuration		4-6 volt 235 AH batteries
<b>Sound Level</b>		
Operator's ear		72 dBa
<b>Warranty</b>	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	



# Model 1530 Specifications

## AUTOMATIC CARPET EXTRACTOR

Feature		English / Metric
<b>Brush System</b>		
Brush length		19-inch/ 482 mm
Brush type		Nylon
Brush RPM		2800
Motor power		0.25 hp/ 0. 19 kW
Motor RPM		1800
<b>Drive System</b>		
Top interim cleaning speed		100 fpm/ 30 mpm
Top deep cleaning speed		50 fpm/ 15 mpm
Max. ramp while cleaning		5°
<b>Productivity</b>		
Theoretical max. per hour: interim cleaning		11,000 ft <sup>2</sup> / 1,022 m <sup>2</sup>
Deep cleaning		5,500 ft <sup>2</sup> / 511 m <sup>2</sup>
<b>Machine Dimensions</b>		
Length		50-inch / 1270 mm
Machine Width		22-inch / 558 mm
Height		42-inch / 1066 mm
Weight		395 lb / 180 kg
<b>Solution &amp; Recovery System</b>		
Solution tank capacity		30 gallon/ 113.6 liter
Recovery tank capacity		21 gallon/ 72 liter
Airflow		99 cfm/ 2.80 m <sup>3</sup> per min
Waterlift		117-inch/ 2971 mm
Vacuum motor power		1.63 hp/ 1.22 kW
Vacuum motor stages		Single 3 stage
<b>Power Consumption</b>		
Total power consumption		14 amps
<b>Sound Level</b>		
Operator's ear		72 dBa
<b>Warranty</b>	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	