



Model E5 Specifications

SELF-CONTAINED CARPET EXTRACTOR

Feature		English / Metric
Brush Drive System		
Brush bristle length		0.9 in / 22 mm
Brush bristle type		Nylon construction, Reverse chevron
Brush diameter		3.5 in / 89 mm
Brush length		15 in / 380 mm
Brush motor power		.4 hp / .30 kW
Brush motor voltage		120 V / 230 V
Brush RPM		1,200 rpm
Motor RPM		2,400 rpm
Chassis/Body Construction		
Chassis construction		Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Wheel descriptions (non-marring)		8 in / 200 mm
Vacuum System		
Airflow at orifice		99 cfm / 2.8 m³/min
Vacuum motor amps		7.1 amps / 3.6 amps
Vacuum motor power		1.2 hp / .89 kW
Vacuum motor stages		2 stage
Sealed waterlift		86 in / 2,180 mm
Machine Dimensions (Handle folded flat for storage)		
Length		27 in / 690 mm
Machine Width		19 in / 480 mm
Height		28 in / 710 mm
Weight		102 lb / 46 kg
Solution & Recovery System		
Solution tank capacity		5 gal / 19 L
Recovery tank wet capacity		5 gal / 19 L
Spray jet count		2-quick connect
Power Consumption		
Amps		10.8 amps / 5.4 amps
Voltage		120 V / 230 V
Watts		1300 watts
Cord		50 ft / 15 m
Electrical Safety Approvals		ETL Tested for UL & CSA Standards
Pump System		
Solution pump pressure		65 psi / 4.48 bar
Solution pump amps		.7 amp / .35 amp
Solution pump flow rate		.7 gpm / 2.6 L/min
Sound Level*		
Decibel rating @ operators ear		69 dBA
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	

* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA