



T16 Battery-Powered Rider Scrubber

Lower your cost of ownership, using innovative cleaning technology that is versatile and easy to maintain - the T16 has it all!

Available Technologies



ec-H2O™ technology



IRIS® Asset Manager



ES® Extended Scrubbing



High capacity battery power sources

Engineered for Productivity









- Optional scrubbing side brush provides a 45 in / 1145 mm scrub path, and a large 50 gal / 190 L solution tank is engineered for maximum cleaning performance and productivity.
- Easy to identify maintenance Touch Points
 ensure daily maintenance items are checked
 and your investment is properly maintained and
 protected.
- 3. Touch-N-Go™ Control Module with 1-Step™
 Button enhance safety with intuitive controls
 located right in front of the operator, eliminating the
 need to remove hands from the steering wheel to
 change scrub settings.
- 4. Reduce repair costs and protect the rear squeegee when backing up with the optional rear squeegee protection kit.

Optional Accessories



Bring high performance spill recovery to hard to reach areas with the optional in-line telescoping vac wand.




Protect operators from falling objects with the optional **overhead guard.**



Protect the T16 from contact damage with the optional severe environment front bumper.

Inside the

T16



- Keep the operator compartment neat and tidy to achieve new levels of productivity.
 The side cargo net and removable tool caddy help the operator stay organized and keep the compartment free of debris.
- Extend component life and reduce maintenance cost with the AC brushless propelling motor that operates more efficiently than traditional DC motors.
- **3. Improve cleaning results** by equipping the T16 with the scrub head that best suits the application.

- **4. Reduce operating costs** with robust machine construction that stands up to severe environments, but is also designed to prevent damage to walls and fragile fixtures.
- **5. Reduce slip/fall and maintenance costs** with the Dura-TrakTM parabolic squeegee system that provides excellent water recovery and can be changed easily without tools.

T16 Specifications

ΔΝΙΝ		

Scrub Path (standard) with Scrubbing Side Brush	910 mm 1,145 mm	
Sweep Path (dual side brushes)	1,170 mm	
Disk brush speed	300 rpm	
Disk brush down force (up to)	114 kg	
Cylindrical brush speed	500 rpm	
Cylindrical brush down force (up to)	91 kg	
Solution tank	190 L	
Solution capacity (ES®)	280 L	
Recovery tank	225 L	
Vacuum fan speed water lift	0.56 kW 14,000 rpm 1,650 mm	
PROPELLING SYSTEM		
Propel speed forward (variable to) Propel speed reverse (variable to)	9 km/h 4 km/h	
Gradeability (transport at gross weight) working (scrubbing)	8°/14.1% 4°/7%	
BATTERY SELECTIONS (EST. CONTINUOUS RUNTIME: ECONOMY MODE)		
Battery optional packages	Wet 235 AH Wet 360 AH	
MACHINE SPECIFICATIONS		
Length basic machine	1,880 mm	

Length basic machine	1,880 mm
Width, body	1,040 mm
Height (top of steering wheel)	1,475 mm
With overhead guard	2,080 mm
Weight empty (no battery)	500 kg
Minimum aisle turn	2,110 mm
Sound level (Disk: Mode #1) (Cylindrical: Mode #1)	68 dBA 71 dBA
Sound pressure level tested per ISO 11201 as recommended by the AACEM and OSHA	

WARRANTY

See your local representative for warranty information

Specifications subject to change without notice.

Tennant-Reinvent how the world cleans

With a vision to become a global leader in sustainable cleaning innovation that empowers our customers to create a cleaner, safer and healthier world, Tennant creates solutions that are changing the way the world cleans.



We are where you are

Tennant has the industry's largest direct sales and service organisation and a well-supported network of authorized distributors worldwide.



Solutions for your unique needs

Whatever your cleaning needs, Tennant offers a variety of high quality equipment to help you increase your cleaning productivity.



Buying, leasing, renting

We offer flexible options to get you the machines you need, however you need them.



Optimise equipment performance and protect your investment with Tennant True® parts and service.

For a demonstration or additional information, call 1800 226 843 or email contactus@tennantco.com

Tennant Australia

Unit 11, 4 Southridge Street Eastern Creek NSW 2766

T: 1800 226 843 (FREE CALL) T: +61 2 9839 9700

www.tennantco.com.au contactus@tennantco.com

Tennant New Zealand

Unit 5, 103 Cryers Road East Tamaki Auckland 2013

T: +64 9 253 9013 F: +64 9 253 9015

www.tennantco.co.nz contactus@tennantco.com