



## T1581

# Ride-on floor scrubber

#### **Productivity boost**

Enhance your cleaning performance and keep your floors looking their best with a versatile and user-friendly mid-sized rideon scrubber. T1581 effectively cleans large hard-floor surfaces with light-to-medium dirt and stains in areas such as logistics, retail and manufacturing.



#### Large tank capacity

Extend runtime with large 63 gal recovery tank capacity and up to 6.4 hours of operation with fully-charged battery.



#### Simple operation

User-friendly operator controls featuring one-button cleaning start-up and three pre-set scrubbing programs simplify operation and training.



#### Versatile cleaning performance

Maintain consistent cleaning results across uneven surfaces with self-leveling brush system that automatically adjusts to the floor surface.

#### Inside the T1581

- Simple operation with three pre-set programs, allowing operator to select the program that best fits their cleaning need.
- 2. Maintain cleaning performance across uneven surfaces with self-leveling system that automatically adjusts the scrub deck height to a floor's surface.
- 3. Quick, mess-free tank draining with large, pinch-style recovery tank drain hose.

- Large-capacity solution tank to clean effectively with fewer dump/fill cycles.
- Consistent water
  pick-up with durable
  v-shaped squeegee
  design and standard
  Linatex® squeegee
  blades.
- 6. Reduce maintenance time by easily accessing daily maintenance and service areas with service-friendly design.



### T1581 specifications

#### **SPECIFICATION**

	41 in	39 in
FEATURE	DISK	CYLINDRICAL
Cleaning path	41.3 in / 1,050 mm	38.7 in / 1,000 mm
Productivity theoretical max*	69,513 ft²/h / 6,458 m²/h	76,262 ft²/h /7,085 m²/h
Scrubbing speed	4.5 mph / 7.2 kmh	
Brush speed	200 rpm	1,000 rpm
Brush pressure	256.6 lbs / 116 kg	82.5 lbs / 37 kg
Solution tank capacity	58 gal / 218 L	
Recovery tank capacity	63 gal / 237 L	
Battery run time**	up to 6.4 hours (wet battery) / up to 6.2 hours (gel battery)	
Battery voltage	36V	
Dimensions (LxWxH)	79 x 54 x 59 in / 2,006 x 1,376 x 1,508 mm	
Squeegee width	54 in / 1,380 mm	
Weight (with heaviest battery)	1,630 lbs / 739 kg	1,685 lbs / 764 kg
External radius (wall to wall)	96 in / 2,440 mm	101 in / 2,570 mm
Maximum ramp climb	16%	
Sound level (operator's ear)***	76 dBA	79 dBA

Specifications subject to change without notice.

For a demonstration or additional information, call +1.800.553.8033 or email info@tennantco.com

**Tennant Company** 

www.tennantco.com

10400 Clean Street Eden Prairie, MN 55344-2650, USA

> USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315

<sup>\*</sup>Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

<sup>\*\*</sup> Run times are based on Continuous Scrubbing Run Times

<sup>\*\*\*</sup> Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA