



REINVENT HOW THE WORLD CLEANS

CS16

Walk-behind micro-scrubber

High productivity for congested areas

The CS16 is a compact, reliable, and user-friendly micro-scrubber that provides effective cleaning in tight spaces. Its easy-to-use controls, low-profile design and ergonomic handle provide easy operation. The CS16 is ideal for hard-to-reach spaces in areas such as hospitals, retail stores and offices.

Available technologies



Lithium-ion batteries



ECO mode

Reduce noise levels and water consumption while increasing run-time with ECO mode.



Compact storage

Easy to operate in tight spaces and store in crowded storage rooms. Adjustable handle makes it easy to maneuver and store.



Easy-to-remove recovery tank

Keep dirty water separate from clean water with separate solution and recovery tanks. Plus easily remove tank for battery access.

Inside the CS16

1. Comfortable grip and adjustable handle for ergonomic operation.

2. 3-Stage vacuum motor for strong water pick-up.

3. Big capacity: 3.9 gal (15 L) solution tank 4.4 gal (16.5 L) recovery tank.
4. Parabolic squeegee shape tracks the movement of the machine for excellent water pick-up.

5. Brush cover made out of durable material.

6. Simple no-tools, no-touch brush change system.



CS16 specifications

FEATURE	SPECIFICATION
Cleaning path	13.8 in / 350 mm
Productivity (per hour) Theoretical Max	13,993 ft² / 1,300 m²
Estimated coverage	10,226 ft² / 950 m²
Max speed	2.2 mph / 3.5 km/h
Brush RPM	140
Brush/pad pressure	55 lbs / 25 kg
Solution tank capacity	3.9 gal / 15 L
Recovery tank capacity	4.4 gal / 16.5 L
Run time AGM standard eco mode Lithium-ion (up to hours)*	60 mins 70 mins 75 mins
Power voltage	24 V
Length x width x height (handle in upright position)	37.4 x 17.7 x 47.2 in / 950 x 450 x 1,200 mm
Length x width x height (storage position with handle folded down)	37.4 x 17.7 x 26.1 in / 950 x 450 x 665 mm
Weight (without Batteries)	79.3 lbs / 36 kg
Sound level (operator's ear)**	68 dBA 66 dBA (eco mode)

Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.
* Run times are based on Continuous Scrubbing Run Times.
** For CE compliance, sound level is measured as an A-weighted sound pressure level per ISO 11201 and reported in accordance with ISO 4871.

For a demonstration or additional information,
call **+1.800.553.8033** or email **info@tennantco.com**

Tennant Company
10400 Clean Street
Eden Prairie, MN 55344-2650, USA
USA/Canada: +1.800.553.8033
Québec: +1.800.361.9050
Overseas: +1.763.540.1315
www.tennantco.com