

T291 Small Walk-Behind Scrubber-Dryer

Small Size. Big Value.

Get a lot of value in a small scrubber-dryer with a simple control panel, comfortable ergonomics, and straight-forward operation. Daily cleaning routine is made easy due to large recovery tank access, easy spin-on, spin-off brush/pad replacement and yellow touchpoints. Perfect for retail settings, schools and hospitals.



Comfortable & Easy to Manuever Maintain operator health and safety with great manueverability, and maximize comfort with adjustable controls.



Simplify Operator Training Easy-to-use control knob that visually shows selected mode. Conveniently select from 13 language options available.



Sustainable Performance Reduce noise levels and water consumption while increasing run-time with ECO mode.

Inside the T291

- 1. Self-leveling scrub head for optimum cleaning performance.
- 2. Simplified operator training with easy-touse pre-programmed cleaning settings, standard and ECO.
- **3. Helpful machine information** is visible with intuitive and large LCD display.
- Simple daily maintenance with large sized recovery tank opening enabling full access and visibility.
- Excellent water pickup from easily adjustable squeegee design and standard Linatex[®] blades.
- Simple no-tools, notouch brush/pad change system simply spin-on, and spin-off.



T291 Specifications

| | SPECIFICATION |
|---|------------------------|
| FEATURE | SELF-PROPEL |
| Cleaning path | 500 mm |
| Productivity (per hour) theoretical max | 2285 m²/hr |
| Estimated coverage (per hour)* | 1436 m²/hr |
| Scrubbing speed | 4.5 kmh |
| Scrub head raise/lower | manual with foot pedal |
| Brush/pad speed | 150 rpm |
| Brush/pad pressure | 19 kg |
| Solution tank capacity | 50 L |
| Recovery tank capacity | 50 L |
| Battery run time - up-to hours** | 3.5 |
| Battery voltage | 24V (2 x 12) |
| Dimensions (L x W x H) | 1327 x 563 x 1033 mm |
| Squeegee width | 815 mm |
| Weight (with heaviest battery) | 178 kg |
| Sound level (operator's ear)*** | 56 dB |

Model shown supplied with pad driver & red pad as standard inclusion. Disk brush available as Aftermarket P&C.

Specifications subject to change without notice.

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

*** Run times are based on Continuous Scrubbing Run Times. *** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

Tennant New Zealand

Unit 5, 103 Cryers Road East Tamaki Auckland 2013

> T: +64 9 253 9013 F: +64 9 253 9015

www.tennantco.co.nz contactus@tennantco.com

Unit 11, 4 Southridge Street Eastern Creek NSW 2766

Tennant Australia

T: 1800 226 843 (FREE CALL) T: +61 2 9839 9700

www.tennantco.com.au contactus@tennantco.com

For a demonstration or additional information, call **+1.800.553.8033** or email **info@tennantco.com**