



REINVENT HOW THE WORLD CLEANS

T391

Mid-size walk-behind scrubber-dryer

Productive and comfortable to operate

Get a lot of return on value with a mid-size scrubber with wide scrub head and large tank capacity. Featuring a simple control panel, comfortable ergonomics, and straight-forward operation. Daily cleaning routine is made easy due to large recovery tank access, easy spin-on, spin-off brush/pad replacement and yellow touchpoints. Perfect for mid-size retail stores, and schools.

Available technologies



Worry-free operation and maintenance with optional lithium ion batteries.



Productivity boost

Get more cleaning done compared to smaller scrubbers with wide scrub path and large solution tank capacity.



Comfortable & easy to maneuver

Maintain operator health and safety with great maneuverability, and maximize comfort with adjustable controls.



Sustainable performance

Reduce noise levels and water consumption while increasing run-time with ECO mode.

Inside the T391

1. **Self-leveling scrub head** for optimum cleaning performance.
2. **Simplified operator training** with easy-to-use pre-programmed cleaning settings, standard and ECO.
3. **Monitor helpful machine information** with intuitive and large LCD display.
4. **Simple daily maintenance** with large sized recovery tank opening enabling full access and visibility.
5. **Excellent water pick-up** from adjustable squeegee design and standard Linatex® blades.
6. **Simple no-tools, no-touch brush/pad change system.**



T391 specifications

FEATURE	SELF-PROPEL	SELF-PROPEL	SELF-PROPEL
Cleaning path	600 mm		700 mm
Productivity (per hour) theoretical max	2697 m ² /hr		3142 m ² /hr
Estimated coverage (per hour)*	1818 m ² /hr		2147 m ² /hr
Scrubbing speed		4,5 kmh	
Scrub head raise/lower	manual with foot pedal		electronic by actuator
Brush/pad speed		200 rpm	
Brush/pad pressure	29 kg		35,4 Kg
Solution tank capacity		70 L	
Recovery tank capacity		70 L	
Battery run time - up-to hours**		3.5 hrs	
Battery voltage		24V (2x12)	
Dimensions (L x W x H)	1279 x 653 x 1033 mm		1279 x 735 x 1033 mm
Squeegee width	815 mm		940 mm
Weight (with heaviest battery)	183 kg		187 kg
Sound level (operator's ear)***		56 dB	

Specifications subject to change without notice.

*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

**Run times are based on Continuous Scrubbing Run Times.

***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

T391 lithium-ion specifications

FEATURE	SELF PROPEL	
Cleaning path	700 mm	
Productivity (per hour) theoretical max	3142 m ² /hr	
Estimated coverage (per hour)*	2147 m ² /hr	
Scrubbing speed	4,5 kmh	
Scrub head raise/lower	manual with foot pedal	
Brush/pad speed	200 rpm	
Brush/pad pressure	29 kg	
Solution tank capacity	70 L	
Recovery tank capacity	70 L	
Battery Type	50 Ah Lithium-Ion	90 Ah Lithium-Ion
Charger Type	Off board charger	On board charger
Battery charging time up-to hours**	2h	7h
Battery run time - up-to hours**	1h30	2h30
Battery voltage	27,8	
Dimensions - L x W x H	1279 x 735 x 1033 mm	
Squeegee width	940 mm	
Weight (with heaviest battery)	185kg	
Sound level (operator's ear)***	56 dB	
Chemical dosing	Standard with ec-H2O NanoClean® technology	

Specifications subject to change without notice.

*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

**Run times are based on Continuous Scrubbing Run Times.

***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information,
call **+32 3 217 94 11** or email **europe@tennantco.com**