



Model T1 Specifications

CORD-ELECTRIC WALK-BEHIND SCRUBBER

Feature	Specification
Scrubbing System	
Cleaning path	15 in / 380 mm
Solution tank capacity	3.0 gallon / 11.4 liter
Productivity (per hour)	
Theoretical Max	15,920 ft ² / 1,480 m ²
Estimated Actual*	8,690 ft ² / 810 m ²
Solution Flow Rate	0.10 gpm / 0.38 lpm
Scrub Motors	0.4 hp / 0.3 kW
Scrub Motor Speed	2400 rpm
Brush down pressure	33 lb / 15 kg
Brush size	3.5 in / 89 mm
Recovery System	
Recovery tank capacity	4.5 gallon / 17.0 liter (Includes demisting chamber)
Vacuum fan	
Motor	1.2 hp / .88 kW
Stages	2-stage
Water lift	86 in / 2180 mm
Airflow	99 cfm / 2.8 m ³ /min
Construction & Power System	
Chassis construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Power supply	120V or 230V
Frequency	50/60 Hz
Cable length	50 ft / 15 m
Electrical Safety Approvals	ETL Tested for UL & CSA Standards
Dimensions / Weight / Sound level	
Length	
Handle in working position	45.4 in / 1150 mm
Handle in folded position	27.3 in / 690 mm
Width	
Base	19.7 in / 500 mm
Squeegee	17.5 in / 440 mm
Height	
Base (folded handle for storage)	23.8 in / 600 mm
With handle up	34 in / 860 mm
Net weight	97 lb / 44 kg
Working weight (with water)	121 lb / 55 kg
Sound level** (operator's ear)	72 dBA
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA