

T300 - DAILY OPERATOR CHECKLIST

PRE-OPERATION CHECKLIST

Check the battery fluid and charge level
Fill the Automatic Battery Watering reservoir with DISTILLED WATER, if equipped.
☐ Fill the Severe Environment [™] (SE) detergent reservoir with detergent, if equipped.
Check the tank cover seals for damage and wear
Clean the vacuum fan inlet filter
Check the condition of the scrubbing brushes (Remove any string, banding, plastic wrap, or other debris wrapped around them)
Check the squeegees for damage, wear and for deflection adjustment
Check the vacuum hose for debris or blockage
Drain and clean the recovery tank
□ ec-H2O NanoClean [™] Scrubbing: Ensure the solution tank is filled with clear cool water only
Check the service records to determine maintenance requirements
POST-OPERATIONAL CHECKLIST
Clean the solution and recovery tanks
Clean the vacuum fan inlet filter
\Box Check the scrub head and brushes for banding, plastic wrap and twine
Check the squeegees for damage or wear
Check the vacuum hoses for debris or blockage
Check the battery charge levels to determine if the batteries need charging
Check the fluid level of all battery cells and place the machine on the charger, if needed.
Fill the Automatic Battery Watering reservoir with DISTILLED WATER, if equipped. List below any problems that occurred during operation.
OPERATOR DATE
SUPERVISOR DATE ¹
