



## T5 Specifications | Disk Walk-Behind Floor Scrubber

<b>Scrubbing System</b>			
Cleaning path (3 paths available)	24 in / 600 mm	28 in / 700 mm	32 in / 800 mm
Solution tank capacity	22.5 gal / 85 L		
Productivity (per hour)			
Theoretical max	26,400 ft <sup>2</sup> / 2,500 m <sup>2</sup>	30,800 ft <sup>2</sup> / 2,900 m <sup>2</sup>	35,200 ft <sup>2</sup> / 3,300 m <sup>2</sup>
Estimated actual* (conventional)	17,875 ft <sup>2</sup> / 1,660 m <sup>2</sup>	20,800 ft <sup>2</sup> / 1,900 m <sup>2</sup>	24,000 ft <sup>2</sup> / 2,200 m <sup>2</sup>
Estimated actual* (ec-H2O NanoClean™)	20,075 ft <sup>2</sup> / 1,900 m <sup>2</sup>	22,750 ft <sup>2</sup> / 2,100 m <sup>2</sup>	26,250 ft <sup>2</sup> / 2,400 m <sup>2</sup>
Solution flow rates			
Standard	.15 gpm / .57 lpm		.22 gpm / .83 lpm
Options	.22 gpm / .83 lpm & .30 gpm / 1.1 lpm		.33 gpm / 1.25 lpm & .44 gpm / 1.66 lpm
Conventional Mode (3 settings)	.25, .35, .45 gpm / .95, 1.3, 1.7 lpm		.30, .40, .50 gpm / 1.1, 1.5, 1.9 lpm
Scrub motors	(2) 0.75 hp / 0.56 kW		
Scrub motor speed	220 rpm		
Brush / pad down pressure	40, 80 & 120 lb / 18, 36 & 54 kg		
Brush / pad driver quantity & size	(2) 12 in / 300 mm	(2) 14 in / 360 mm	(2) 16 in / 410 mm
<b>Recovery System</b>			
Recovery tank capacity	27 gal / 102 L (Includes demisting chamber)		
Vacuum fan			
Motor	0.85 hp / 0.640 kW		
Stages	3-stage		
Water lift	62 in / 1,570 mm		
<b>Propelling &amp; Power System</b>			
Propel speed (variable to)			
Transport	2.7 mph / 4.3 km/h		
Scrubbing	2.5 mph / 4.0 km/h		
Batteries (24 V system, charger included)			
Standard / run time**	(4) 6V, 235 AH / Up to 5 hours		
Optional Sealed (AGM) / run time**	(4) 6V, 200 AH / Up to 4 hours		
Gradeability (ramp climb)			
Scrubbing / transporting (full)	3.0° / 5.0°		
Trailer ramps (empty)	11°		
Speed control	Top Speed Potentiometer & Variable Speed Trigger		
<b>Dimensions / Weight / Sound level</b>			
Length	53 in / 1,350 mm	55.7 in / 1,410 mm	58 in / 1,480 mm
Width			
Body	23 in / 580 mm		
Scrub head	25.4 in / 640 mm	29 in / 740 mm	33 in / 840 mm
Squeegee	35.7 in / 910 mm	41.3 in / 1,050 mm	46.6 in / 1,180 mm
Height	44 in / 1,120 mm		
Net weight			
Less batteries	316 lb / 143 kg	365 lb / 152 kg	377 lb / 158 kg
With batteries (4) 6V 235 AH	580 lb / 263 kg	609 lb / 276 kg	621 lb / 282 kg
Minimum aisle turn:	53 in / 1,350 mm	59 in / 1,500 mm	64 in / 1,630 mm
Sound level*** (operator's ear)	67 dBA		
<b>Warranty</b>	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.		

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

\*\* Run times are based on Continuous Scrubbing Run Times.

\*\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA