



## T5 - DAILY OPERATOR CHECKLIST

### PRE-OPERATION CHECKLIST

- Check the battery fluid and charge level
- Check the tank cover seals for damage and wear
- Clean the vacuum fan inlet filter
- Check the condition of the scrubbing brushes  
(Remove any string, banding, plastic wrap, or other debris wrapped around them)
- Check the squeegees for damage, wear and for deflection adjustment
- Check the vacuum hose for debris or blockage
- Drain and clean the recovery tank
- FaST Scrubbing: Check the optional FaST—PAK concentrate agent level
- FaST Scrubbing: Ensure that all conventional cleaning agents are drained and rinsed from the solution tank
- FaST or ec-H2O Scrubbing: Ensure that the solution tank is filled with **clear cool water only**
- Check the service records to determine maintenance requirements

### POST-OPERATIONAL CHECKLIST

- Clean the solution and recovery tanks
- Clean the vacuum fan inlet filter
- Check the scrub head and brushes for banding, plastic wrap and twine
- Check the squeegees for damage or wear
- Check the vacuum hoses for debris or blockage
- Check the battery charge levels to determine if the batteries need charging
- Check the fluid level of all battery cells and place the machine on the charger, if needed

List below any problems that occurred during operation.

---

OPERATOR \_\_\_\_\_ DATE \_\_\_\_\_

SUPERVISOR \_\_\_\_\_ DATE \_\_\_\_\_

---

<sup>1</sup> E:\Techtr\Machines\T5\T5-Opck.doc