

Working for a cleaner, safer world™

6550 Power Sweeper



Outstanding Sweeping

If you want a sweeper that lasts, the Model 6550 power sweeper defines industrial durability. This rugged machine takes on any industrial surface, smooth or rough, indoor or outdoor, with equal results. Plus, the 6550 features the revolutionary VCS™ filtershaking system, which maximizes the machine's dust-free performance.

Tough on Dirt, Easy on Your Operator

A rider sweeper can be built tough but still cause fatigue. The Model 6550 maximizes operator comfort with ergonomic features such as power/tilt steering and a soft-ride seat. Plus, a standard overhead guard provides added protection.

Productivity-Enhancing Features

A 26-in. (660-mm) side brush together with a 45-in. (1145-mm) main brush provides a 61.5-in. (1565-mm) sweeping path. And a retractable, spring-loaded arm allows the side brush to safely extend into corners and other hard-to-reach areas.

Match Power Source to Your Needs: G, LPG, D, and E

The 6550-E battery-powered sweeper features fume-free quieter operation (75 dBa), and low maintenance for greater economy with industrial cleaning performance.



The patented new VCS™ filtershaking system incorporates breakthrough technology that makes all manual filter-shaking systems obsolete. Includes a clogged-filter indicator as well as a timed 10-second shakedown.







A stress-tested, steel-plate frame encases the 6550 to protect both internal components and the operator.



Picks up even the rocky debris found in brickyards and cement plants.



II-Speed™ sweeping controls the dirt, litter and dust of almost any surface, no matter how rough the environment.



The Model 6550

- 1 VCS™ system features dual-sealed filter and timed shaking system for greater cleaning efficiency.
- 2 Dual dust skirts seal main brush door compartment to prevent dust and debris from escaping.
- 3 Low noise level (G, LPG, D) makes the 6550 more comfortable to operate (80 dBA at normal operating speed).
- Simple brush replacement without tools means machine is up and running again quickly.

Model 6550 Specifications*

Propelling System

Gradeability 10.0 deg/18% Full hopper Empty hopper 15.0 deg/27% Speed forward (variable to) 16.1 km/h 10.0 mph Speed reverse (variable to) 2.5 mph 4.0 km/h **Sweeping System** Coverage rate per hour Average (5 mph, 6 inch overlap) 122,100 ft² 11,350m² 270,600 ft² Maximum (full speed, no overlap) 25,140 m² 1565 mm 61.5 in Cleaning path Main brush length (tubular) 1145 mm 45 in Sidebroom diameter (disk) 26 in 660 mm

14 ft³

60 in

1200 lb

400 L

545 kg

1525 mm

Dump height

Hopper capacity

Volume capacity Weight capacity

lachine Dimensions		
Length	93.0 in	2360 mm
Width	62.5 in	1590 mm
Height without overhead guard	58.0 in	1475 mm
Height with overhead guard	82.0 in	2080 mm
Net weight	3675 lb	1670 mm
Turning radius	65 in	1650 mm
Minimum aisle turn (left)	113 in	2870 mm

Tennant Value Added Equipment Includes:

Multi-level dump Perma-filter™
Il-Speed™ cleaning Color-coded wiring
Hopper access door Industrial radiator
Wrap-around bumper Vacuum fan shutoff
T-beam frame construction No-tool brush change
Audio-visual backup alarm Overhead guard

Optional Equipment

Light packages Vacuum wand
Sidebrush dust control Enclosed cab
Sealed alternator SB2 auxiliary side brush

Model 6550E Specifications*

Propelling System

Gradeability
Full hopper
Empty hopper
Speed forward (variable to)
Full hopper
Speed forward (variable to)
Speed reverse (variable to)

Sweeping System

Coverage rate per Hour

Average (4 mph, 6 inch overlap) 97,600 ft² 9070 m²

Maximum (full speed, no overlap) 143,400 ft² 13,325 m²



The Model 6550's optional SB2 auxiliary sidebrush cleans areas not accessible to regular sweepers.



While the main brush sweeps debris on street level, the SB2 cleans up on the curb.

Working for a cleaner, safer world TM

Tennant Company and Castex, Incorporated offer the most complete lines of floor and surface maintenance equipment, floor coatings, brushes, and cleaning detergents in the world. Our sales and service networks are able to provide you with integrated custom cleaning solutions to meet any floor care need.

ISO 9001 Certified



The Tennant Total Solution Includes:

- •Factory-Direct Sales
- Authorized Floor Coatings Contractors
- •Factory-Direct Service
- •Authorized Sales & Service Distributors



Tennant Company

P.O. Box 1452 Minneapolis, MN U.S.A. 55440 Call toll-free: 1-800-553-8033 In Quebec call: 514-335-6061

Fax: 612-540-1437 www.tennantco.com

^{*} Subject to change without notice. (Some options may not be available in all countries.)