



# S9 Sweeper Daily Operator Checklist

## Read and understand the Operator's Manual



**Before Operation:**

- Confirm the battery is fully charged.
  - o Connect the battery charger AC cable and plug in the charger, if required.
- Move the dust filter cleaning handle back and forth a few times to clean the filter.
- Lift the hopper locking lever, remove and empty the hopper.
- Remove any wire, string, or twine that may have become wrapped around the side brushes.
- Remove any wire, string, or twine that may have become wrapped around the main brushes.
- Slide the hopper into the machine until the locking lever engages.
- Adjust the rear main brush height, if required.
- Adjust the handle height, if required.
- Turn on the key switch.
- Lower the side brushes, if they will be used.
- Choose the correct operational setting for conditions.
  - o From left to right, the first button turns on the main brushes, the side brushes and the vacuum fan.
  - o The second button turns on only the main brushes and the side brushes.
  - o The third button turns on only the main brushes and the vacuum fan.
- Control propelling speed, as needed for conditions.

**After Operation:**

- Turn off the key switch.
- If the side brushes were used, raise them.
- Move the dust filter cleaning handle back and forth a few times to clean the filter.
- Lift the hopper locking lever, remove and empty the hopper.
- Inspect the dust filter.
  - o If the filter needs to be removed for cleaning or replacement, move the two retaining levers to the unlocked position, lower and remove the filter from the retainer.
  - o Clean and reinstall the filter.
  - o The decal indicates the correct direction for the filter installation. (Arrow Pointing Up)
- Slide the hopper into the machine and the locking lever will automatically engage.
- Connect the battery charger AC cable and plug in the charger.

List Machine Issues, if needed:

---



---

**Operator's Signature:** \_\_\_\_\_

**Supervisor's Signature:** \_\_\_\_\_