

V-LWU-13 | LIGHT-WEIGHT UPRIGHT VACUUM



Combining a high performance clean with ultra light, user-friendly design.

Proven performance

Standard with HEPA 2-stage filtration for improved air quality, the vacuum's cleaning performance is also certified Gold by the Carpet and Rug Institute's (CRI) Seal of Approval program.

Increased ease-of-use

Easily transportable 8lb/3.6kg vacuum easily maneuvers to help minimize operator fatigue and is up to two times lighter than many competitive models. Clean a variety of flooring surfaces quickly and efficiently with flexible settings and adjustable sound level.

Reliable durability

Major components have been proven in commercial application for over five years. Balancing the performance, durability, low operating costs and reduced weight of this vacuum makes it a great value at an affordable price.

Key Product Features

- Maximize cleaning efficiency with automatic pile height adjustment that adapts to a variety of floor surfaces and reduces premature brush wear.
- Clean without disruption in noise-sensitive environments using quiet mode, at less than 70 dBA sound level.
- Reduce maintenance costs and downtime with no-tool brush replacement.

V-LWU-13 | LIGHT-WEIGHT UPRIGHT VACUUM



FEATURES	SPECIFICATIONS*
Product Name	V-LWU-13
Vacuum System Airflow at 2 in / 50 mm orifice, high speed Vacuum motor hp Vacuum motor type Vacuum motor amps Water lift at sealed orifice	106 cfm / 3 m ³ /m 1.6 hp / 1.19 kW Single stage, thermal protected, direct air 6 A 71 in / 1804 mm
Brush Drive System Brush belt description Brush type Brush size Brush height	Round drive belt 13 in / 330 mm wooden brush roll with natural bristles 2.25 / 57 mm in diameter Automatic, self-adjusting
Filtration Double filtration system Double filtration description Vacuum bag capacity	HEPA paper bag, cloth bag High efficiency (99.97%) at 0.3 micron Fill design, 11.3 qt / 10.7 L
Electrical Power cord length	50 ft / 15 m, 3 wire commercial safety-yellow cord with thermal protection switch
Chassis/Body Construction Construction	Injection molded ABS
Dimensions / Weight / Sound Level Length Width Height Weight Sound level (at operator's ear), low speed	13 in / 330 mm 14.75 in / 370 mm 44 in / 1120 mm 8 lb / 3.6 kg < 70 dBA
Approvals	UL, CRI SOA Gold
Warranty	See your sales representative or authorized distributor for complete warranty details.

*Specifications subject to change without notice